

Ten Oaks solid hardwood flooring adds timeless beauty and style to any room, home, or commercial space. Our state-of-the-art manufacturing operation, located in the beautiful foothills of Virginia's Blue Ridge Mountains, sources 100% of our fine Appalachian hardwood from Verified Sustainable Hardwood Forests. Our flooring exemplifies a tradition of excellence born of over a century of combined experience with an eye to the future in our revolutionary Six Side Seal®.

What is a Sealed Unfinished Floor?

Ten Oaks uses a patented process to coat the bottom, sides, ends, and top of each piece of unfinished flooring (even down in the grooves).

The moisture resistant seal keeps each piece of flooring at the dimensional specifications of its manufacture. The floor can be installed the same day it is delivered to the jobsite as long as the site meets NWFA specifications. The Six Side Seal® protects your floor from cupping or crowning by slowing the absorption of moisture during the humid seasons and the drying of the wood in the arid seasons. Time-tested and true, our Six Side Seal® is the preferred floor in some of the most dynamic climates in the country.

Combined with Ten Oaks' precise manufacturing methods, the Six Side Seal® provides the perfect unfinished floor.

Solid Oak Hardwood Flooring

Board Width	21/4", 31/4"
Board Thickness	3/4"
Board Length	Random
Sealed? Yes	
Edge Description Square Edge	
Species	Oak
Color	Red, White
Grade	Select & Better
	#1 Common
	#2 Common
Finish	Jobsite or Prefinished
Installation Method	Nail, Glue
Installation Grade	Above, On

Warranty

Ten Oaks warrants the structural integrity of its products for life, and our prefinished wear surface for 20 years. Be aware that most flooring problems are due to improper installation and are therefore not covered by your factory warranty. Please make sure that you use a reputable installer and install according to NWFA guidelines. See full warranty at www.tenoaksflooring.com/limited-warranty for more detailed information.

Benefits of a Ten Oaks Sealed Unfinished Floor

- Requires no acclimation (as long as job site meets NWFA specifications.)
- Keeps flooring "manufacture fresh", enabling a more accurate match and less overwood.
- · Increases dimensional stability for the life of the floor.
- · Incorporates anti-mold, anti-mildew, and anti-bacterial additives under and around each piece of flooring.
- · Protects floor from dirt and spills on jobsite before sanding.
- Highlights color and character for better grading at the mill and better installation at the jobsite.
- Provides physical barrier to insect infestations.









For more information, visit our website **www.tenoaksflooring.com**